Panel Panel Panel Panel Panel Size 12 inch Screen Ratio 16:9 Potch 0.264mmx0.264mm(H,V) Resolution 1366x768 Contrast 500:1 Brightness (cd/m2 400cd/m2 Response time(m5 fms Viewing Angle 178*/178* Color 16.7M Working life 50,000 hours Industrial metal shell, wear-resistant vibration, anti-jamming, challenging harsh environments, super heat Can do high-definition digital TV, high-definition industrial display, computer display, high-definition photographic display, high-definition photographic display, home display high-definition photographic display, high-definition photographic display HDMI, 1080P display 4D color management and image processing Multiple mode selection inputs High-brightness, full-screen display uniformity, no different Adaptive 3D Digital Noise Reduction, DLTL (Digital Bright	12 inch CCTV monitor							
Panel Pa								
Interface	12"	MC1208			Size 12 inch Screen Ratio 16:9 Potch 0.264mmx0.264mm(H,V) Resolution 1366x768 Contrast 500:1 Brightness (cd/m2 400cd/m2 Response time(ms 5ms Viewing Angle 178*/178* Color 16.7M Working life 50,000 hours Industrial metal shell, wear-resistant vibration, anti-jamming, challenging harsh environments, super heat Can do high-definition digital TV, high-definition industrial equipment display, high-definition photographic display, computer display, high-definition photographic display HDMI, 1080P display 4D color management and image processing Multiple mode selection inputs High-brightness, full-screen display uniformity, no difference Adaptive 3D Digital Noise Reduction, DLTL (Digital Brightn DCT (digital chroma instant enhancements), autom Automatic skin tone correction Unique DNX (Digital Natural Expression), motion compensation image processing technology Long life, low radiation, environmental protection Light Sensor			
OSD Control Multiple languaged esse, Italian, German, Dutch, Russian(Oplon) Working temperatu O°C - 50°C Working Humidity 10-90% Installation Packaging size 10 pcs carton Size: 36'70'61cm Power consumption Less 20W Application range The power consumption Less 20W Application to see 35. camera and sides camina Application to serial HD equipment Application to security/monitor screen Remark:						HDMI USB AV Audio input Audio output Power	HDMI interface(1080p/1080i/720p) USB 1 vedio ,2 audio PC audio input PC audio output(Digital) DC 12V M	
Working Humidity 10-90% Installation Packaging size 10 pcs carton Size: 36*70*61cm Power consumption Less 20W Application targe The power was and side game Application to sides Six carers and side game Application to seed Six carers and side game Application to seed Six carers and side game Application to seed six carers and side game Application to security/monitor screen Application to security/monitor screen Application to security/monitor screen					OSD Control	Multiple language	English, French, Spanish, Polish, Portugu sese, Italian, German, Dutch, Russian (Opti	
Installation desktop, wall mount Packaging size 10 pcs carton Size: 36*70*61cm Power consumption Less 20W Application to rege White have been despited to make the second of the sec					Working temperatu	0°C - 50°C	C	
Packaging size 10 pcs carton Size: 36*70*61cm Power consumption Less 20W Application range The data care with closer and Popular are find on the property of the construction of the c					Working Humidity	10-90%		
Application to weldoo Stat camera and violes game. Application to delete Stat camera and violes game. Application to security/monitor screen Power consumption Less 20W Application to weldoo Stat camera and violes game. Application to media screen for industrial high-end equipment Remark:					Installation	desktop, wall mount		
Application range We of Activate also used of Construction and an analysis of the control of th					Packaging size	10 pcs carton Siz	Size: 36*70*61cm	
Application to video StR camer and video quadratic video quadr					Power consumptio	Less 20W		
Remark :	The first diverse was made and will only the state of the							
		Ap	plication to security/mo	onitor screen	Application to monitor screen fo	r industrial high-end equip	ment	
1. Trade Term:EXW	Remark	K :						
	1. Trade	Term:EXW						

Delivery time: 15 days
 Period of validity:10 days.

5. Warranty: 2 Years Guarantee.

4. Payment: 30% T/T in advance,the 70% balance can be paid before shipment.