

<b>Item No.:</b>	<b>MO185W</b>
<b>Description:</b>	<b>18.5 inch Flat Screen Touch Monitor Projected Capacitive Touch screens. Vandal proof Metal Frame</b>



### Specification

<b>General</b>	
Series	FLAT Screen
LCD Type	18.5" Active matrix
Video Input	VGA and HDMI
OSD controls	Allow on-screen adjustments of Brightness, Contrast Ratio, Auto-adjust, Phase, Clock, H/V Location, Languages, Function, Reset
Power Supply	Type: External brick Input (line) voltage: 100-240 VAC, 50-60 Hz Output voltage/current: 12 volts at 4 amps max
Mount Interface	1)VESA 75mm and 100mm 2)Mount bracket, horizontal or vertical
<b>LCD Specification</b>	
Active Area(mm)	410(H)x230mm(V)
Resolution	1366x768@75Hz
Dot Pitch(mm)	0.264x0.264
Nominal Input Voltage VDD	+5.0V(Typ)
Viewing angle (v/h)	85°/88°
Contrast	1000:1
Luminance(cd/m2)	300,1000 NITS
Response Time(Rising)	5s/5s
Support Color	16.7M
Backlight MTBF(hr)	30000
<b>Touchscreen Specification</b>	
Type	Projected Capacitive touch screen
Multi touch	10points touch
Touch Life Cycle	10 millions
Touch Response time	8ms
Touch System Interface	USB interface
Power consumption	+5V@80mA
<b>External AC Power Adapter</b>	
Output	DC 12V /4A
Input	100-240 VAC, 50-60 Hz
MTBF	50000 hr at 25°C
<b>Environment</b>	
Operating Temp.	0~50°C
Storage Temp.	-20~60°C
Operating RH:	20%~80%
Storage RH:	10%~90%
<b>Components</b>	
USB Cable 180cm*1 Pcs, VGA Cable 180cm*1 Pcs, Power Cord with Switching Adapter *1 Pcs,	